

1. SCOPE 应用范围

This specification is applied to SHANGHAI HITACHI rotary compressor.
此规格适用于上海日立电器有限公司生产的旋转式压缩机。

2. SPECIFICATION OF COMPRESSOR 压缩机规格

2.1 Model

型号	ASH201SN-C8LU
----	---------------

2.2 Rated Voltage-Frequency-Phase

额定电压/频率/相数	208~230V/60Hz/单相
------------	------------------

2.3 Application

应用	Air Conditioning 空调机
----	-------------------------

2.4 Refrigerant

制冷剂	R—410A
-----	--------

2.5 Compressor Cooling

压缩机冷却	Forced air 强制空冷
-------	--------------------

2.6 Displacement

排气量	20.1ml/rev
-----	------------

2.7 Rated capacity(see*)

额定冷量(见*)	5860W(5038Kcal/h)
----------	-------------------

2.8 Motor input(see*)

电机输入功率(见*)	2035W
------------	-------

2.9 COP

能效比	2.88 $COP = \frac{\text{Rated capacity 额定冷量 (W)}}{\text{Motor input 电机输入功率 (W)}}$
-----	---

2.10 Current

电流	9.95 A
----	--------

2.11 Allowable amount of
refrigerant charge

制冷剂充注允许量	2100g
----------	-------

2.12 Amount of oil charge

油充注允许量	600 ± 20 ml(Initial) 600 ± 20 ml(最初)
--------	---

2.13 Oil

油	HAF68D1 or equivalent
---	-----------------------

2.14 Space volume of inner case

壳体内容积	1990ml
-------	--------

2.15 Net weight

净重	17.5 kg incl.oil 17.5kg 包括油
----	--------------------------------

	<p style="text-align: center;">SUBJECT</p> <p style="text-align: center;">Model ASH201SN-C8LU SPECIFICATION</p> <p style="text-align: center;">ASH201SN-C8LU 规格书</p>	<p style="text-align: right;">PAGE : 2/23</p>
<p>2.16 Hermetic Terminal 密封接线柱</p>	<p>1/4"quick connect type 1/4" 快速连接型</p>	
<p>2.17 Motor</p> <p>Type</p> <p>Capacitor</p> <p>Locked rotor amps</p> <p>Approved voltage range</p> <p>Winding resistance(M/S)</p> <p>电机</p> <p>形式</p> <p>电容器</p> <p>堵转电流</p> <p>电压变动范围</p> <p>电阻(主线圈/副线圈)</p>	<p>Permanent Split Capacitor</p> <p>45 μF /400 Volts</p> <p>52A (230V/60Hz)</p> <p>Rated voltage \pm 10%</p> <p>1.37/2.79 (at 75)</p> <p>PSC</p> <p>45 μF/400V</p> <p>52A (230V/60Hz)</p> <p>额定电压 \pm 10%</p> <p>1.37/2.79 (at 75)</p>	
<p>2.18 Rated conditions</p> <p>额定工况</p>	<p>Voltage</p> <p>Evaporating temp.</p> <p>Condensing temp.</p> <p>Liquid temp. entering expansion valve.</p> <p>Return gas temp.</p> <p>Ambient temp.</p> <p>电压</p> <p>蒸发温度</p> <p>冷凝温度</p> <p>膨胀阀前液体温度</p> <p>回气温度</p> <p>周围温度</p>	<p>208 ~ 230 V</p> <p>7.2</p> <p>54.4</p> <p>46.1</p> <p>35</p> <p>35.0</p> <p>208 ~ 230V</p> <p>7.2</p> <p>54.4</p> <p>46.1</p> <p>35</p> <p>35.0</p>
<p>2.19 Starting performance</p> <p>起动性能</p>	<p>(1) The starting voltage should be as follows.</p> <p>(2) The starting pressure should be balanced between the suction and discharge of the compressor and should be adjusted to the following table.</p> <p>(3) The temperatures of the compressor enclosure should be more than 20 continuously at the following table.</p> <p>(1) 起动电压如表 1 所示。</p> <p>(2) 起动压力必须在吸气压力及排气压力之间进行平衡，并按下表予以调节。</p> <p>(3) 在起动工况下，压缩机环境温度要保持在 20 以上。</p>	

TABLE 1 表 1


Starting Conditions 起动工况		Spec 规格
Motor temperature 电机状态	Pressure 平衡压力 MPa{kgf/cm ² G}	Starting voltage 起动电压 (V ₂)**
Cold-Starting 冷起动 Cold state (room temperature) 冷工况(室温)	1.703{16.36}	Below 85% of rated voltage 不高 于额定电压的 85%
Hot-Starting(Standard) 热起动(标准) Hot state after operated under standard load condition 在标准负载下运行后的工况	1.703{16.36}	Below 85% of rated voltage 不高 于额定电压的 85%
Hot-starting(Overload) 热起动(超负荷) Hot state after operated under overload condition 在超负载条件下运行后的工况	1.860{17.96}	Below 90% of rated voltage 不高 于额定电压的 90%

*. Rated capacity and motor input are measured by secondary Refrigerant calorimeter Methods of JIS B8606 by Shanghai Hitachi Electrical Appliances Co., Ltd. Allowable capacity should be more than 95% of the rated capacity and Allowable motor input should be less than 107% of rated motor input.
额定冷量和电机输入功率由本公司根据 JIS B8606 的第二制冷剂法测试。允许冷量应为额定冷量的 95% 以上，允许电机输入功率应为额定电机输入功率的 107% 以下。

** . V₂ means minimum voltage measured between pins of hermetic terminal at the compressor starts.

V₂ 是指压缩机起动时所测密封接线柱端子间的最小电压。

V₂



Time 时间

***. The suction pressure is measured on the position above the filter of accumulator.
吸入压力测定位置在储液器滤网上面。

SUBJECT

Model ASH201SN-C8LU SPECIFICATION
ASH201SN-C8LU 规格书

PAGE : 4/23

3. PARTS AND DRAWING LIST 零件及图纸清单

PARTS NAME 零件名称			QTY/SET 数量/套	DRAWING NO. 图纸号	REMARKS 备注
Compressor 压缩机			1	4CYCH0102	Dimensioned sketch 尺寸简图
Mounting parts 安装件	RUBBER GROMMET	避振脚	3	4CYC00008	
	Bolt	固定螺栓	-	4CYC00175	*
	Nut	固定螺母	-	(M8)	*
Electrical parts 电器部件	OTerminal-Cover	接线盒盖	1	4CYC00101	
	Gasket	接线盒盖垫片	1	4CYC00102	
	Nut	固定螺母	1	3CYC00004	
	Rubber-Washer	固定垫圈	1	4CYC00174	
	Running Capacitor	运转电容	-	4CYC00173	*
				4CYC00737	Wiring Diagram 接线图 Performance curve 性能曲线

* Out of supply, for reference. 不提供, 仅供参考。

4. CHARACTERISTICS

一般特性

4.1 Residual moisture 150mg MAX

残余水分含量 以下

4.2 Residual impurities 100mg MAX

杂质含量 以下

B
图样本部
4CYCH0102

图号	名称	年月日	设计	审核	编号	履历	年月日	修正	审查
①	蓄液器	07.03.01	侯研	侯研	①				
②	蓄液器	07.03.01	侯研	侯研	②				
③	蓄液器	07.03.01	侯研	侯研	③				

THE CYLINDR WHICH LESS THAN DIAMETER 12.80mm CAN PASS THE PIPE, BUT THE CYLINDR WHICH MORE THAN DIAMETER 11.0mm CAN'T PASS THE PROHIBITIVE POSITION.
 内径小于φ12.80的圆柱可以穿过φ11.0的孔,反之无法通过

DISCHARGE PIPE (NTS)
排气管

SECTION PIPE (NTS)
吸气管

SUCTION 吸气管

DISCHARGE 排气管

THE ACCUMULATOR APPEARANCE IS SUBJECT TO MATERIAL OBJECT.
蓄液器外观以实物为准

NOTE:
注: 1. THE TORQUE ENFORCED ON THE NUT IS 1.5±0.3N.m.
接线盒固定螺母的安装扭矩为 1.5±0.3N.m.
2. PUTTING OUT RUBBER PLUG WHEN FIXING EARTH PARTS.
接地螺栓橡胶塞拔去后, 安装接地附件。

DIMENSION, mm
尺寸单位: mm

适用机种
ASH201SN-C8LU
ASH218AN-CFLU

PROJ	SCALE	NTS
PROJECTION	SCALE	NTS
DESIGNER	DATE	07.03.01
CHECKER	DATE	07.03.01
APPROVER	DATE	07.03.01
DATE	DATE	07.03.01
TITLE	DIMENSIONED SKETCH	
NO.	4CYCH0102	

